## Information about norm changes

In line of the international adjustments of several norms following have been changed:

	OLD	NEW	NEW	NEW
Article	DIN	DIN-ISO	DIN-EN-ISO	DIN-EN
Taper pins unhardened	(1)			22339
Parallel pins	(7)		2338	
Tolerance area				
Slotted cylinder head screws	(84)		1207	
Slotted cheese head screws	(85)		1580	
Washers with lug	(93)		without substitution withdraw	vn
Split pins	(94)		1234	
Washers	(125 - 1)		7089	
without chamfer	(125 - 2)			
Washers	(125 - 1)		7090	
with chamfer	(125 - 2)			
Washers	(126)		7091	
Spring washers, with bend or sleek ends	(127)	without substitution withdrawn		
Spring washers	(128)	without substitution withdrawn		
Curved spring washers	(137)		without substitution withdraw	vn
Threaded pin with slot and dog point	(417)			27435
Threaded pin with slot and shaft	(427)		2342	
Washers with external tab	(432)	without substitution withdrawn		
Washers for cylinder head screws	(433-1)		7092	
product class A thru hardness 250HV				
Washers for cylinder head screws	(433-2)		7092	
product class A thru hardness 300HV				
Threaded pins with slot and	(438)			27436
cup point				
Hexagon nut thin type (with chamfer) metric fine thread	(439)	8675	8675	

Hexagon nut thin type (with chamfer)	(439-2)	4035		4035		
Hexagon nut thin type (without chamfer)	(439-1)	4036		4036	П	
Washers for wooden construction	(440)			7094	П	
Washers with 2 lugs	(463)		with	out substitution withdra	wn	
Knurled screws (high form) with slot	(465)		with	out substitution withdra	wn	
Safety cup	(526)		with	out substitution withdra	wn	
Threaded pins with slot and flat point	(551)			4766		24766
Threaded pins with slot and point	(553)				П	27434
Hexagon nuts	(555)			4034	П	
Hexagon screws with thread nearly under the head (adjusting screws)	(558)			4018	П	
Hexagon bolt (partial thread)	(601)			4016	П	
Hexagon fit bolts with short threadpoint	(610)		with	out substitution withdra	wn	
Hexagon key	(911)	2936				
Hexagon socket head cap screw	(912)			4762	П	
Threaded pins with with internal hexagon and flat point	(913)			4026	П	
Threaded pins with with internal hexagon and point	(914)			4027	П	
Threaded pins with with internal hexagon and dog point	(915)			4028	П	
Threaded pins with with internal hexagon and cup point	(916)			4029	П	
Threaded pins with slot and dog point	(926)		without substitution withdrawn			
			possibly use DIN EN 27435			
Hexagon bolts (partial thread)	(931)			4014		
Hexagon set	(933)			4017		
Hexagon nuts, typ 1, product class A + B	(934)			4032		
Hexagon nuts, typ 2, product class A + B	(934)			4033		
Hexagon nuts, typ 1, product class A + B, fine thread	(934)			8673		
Hexagon thin nuts	(936)		without substitution withdrawn			
Castle nut (thin type)	(937)	without	substitu	ution withdrawn possibly	use	DIN 979
Stud screw MFS part 1 (threaded end ~ 2d) form A	(949-1)		with	out substitution withdra	wn	
Stud screw MFS part 2 (threaded end ~ 2,5d) form B	(949-2)		with	out substitution withdra	wn	
Hexagon bolts (partial thread) fine thread	(960)			8765		
Hexagon setscrews fine thread	(961)			8676		
Countersunk screws with slot	(963)			2009		
Raised countersunk screws with slot	(964)			2010		

Countersunk screw with cross recess	(965)		7046-1	
Countersunk screw with cross recess	(965)		7046-2	
Raised countersunk screw with cross recess	(966)		7047	
Hexagon nut, part 1, product class A + B, fine thread	(971)		8673	
Hexagon nut, part 2, product class A + B, fine thread	(971)		8674	
Threaded bolt	(975)	V	vithout substitution withdrav	vn
			possibly use DIN 976-2	
Threaded bolt with metric thread	(975)	V	vithout substitution withdrav	vn
			possibly use DIN 976-1	
Hexagon welding nut with flange	(977)		21670	
Locking nut (all-metal) type 2 metric	(980)		10513	
fine thread				
Locking nut (all-metal nut) type 2	(980)		7042	
Locking nut (heavy form)	(982)		7040	
Locking nut (non-metal) tpye 1	(982)		10512	
metric fine thread				
Locking nut (thin type) non-metal element	(985)		10511	
Nails for lightweight building board	(1144)			10230-1
Round nails countersunk	(1151)			10230-1
Round nails with swaged head	(1152)			10230-1
Clout nails	(1160)			10230-1
Bolts without head	(1433)			22340
Bolts with small head	(1434)			22341
Bolts with small head	(1435)			22341
Bolts with big head	(1436)			22341
Washers for bolts, product class A	(1440)			28738
Bolts without head	(1443)			22340
Bolts with head	(1444)			22341
Cylinder pins with pilot	(1470)		8739	
Grooved taper pins	(1471)		8744	
Close-tolerance grooved pins	(1472)		8745	
Cylinder pins with chamfer	(1473)		8740	
Half length everse grooved pins	(1474)		8741	
	· · · · · · · · · · · · · · · · · · ·			

Third length center grooved pins	(1475)	8742		
Groove pins	(1476)	8746		
Groove pins with countersunk head	(1477)	8747		
Spanner nuts forged (open form)	1480	with		
		DIN 34828:2005		
		alternative for		
		DIN 1480:1975		
Tolerance zone				
Spring pins (-sleeve), slotted, heavy construction	(1481)	8752		
Coupling screws with flanged nut and basis for	(5917)	withdrawn, no demand		
twin sleeper				
Cylinder pins, hardened	(6325)	8734		
Clip bolts	(6378)	withdrawn, no demand		
Lock washers	(6797)	without substitution withdrawn		
Serrated lock washers	(6798)	without substitution withdrawn		
Parallel keys	(6885 - 2)	without substitution withdrawn		
Combi-screws steel with flat washers	(6900 - 1)	10644		
grade of the washers 200HV and 300 HV				
Combi - screws with spring lock washer	(6900 - 2)	without substitution withdrawn		
Combi - screws with circlip	(6900 - 3)	without substitution withdrawn		
Combi - screws with serrated lock washer	(6900 - 4)	without substitution withdrawn		
Combi - tapping screws with flat washer	(6901)	10510		
Flat washers for combi - screws - small, normal and big series -	(6902)	10673		
productclass A				
Flat washers for combi - tapping screws - small, normal and big series -	(6903)	10669		
productclass A				
Spring lock washers for combi - screws	(6904)	without substitution withdrawn		
Circlips for combi - screws	(6905)	without substitution withdrawn		
Lock washers external serrated for combi - screws	(6907)	without substitution withdrawn		
Circlips with safety ring	(6913)	without substitution withdrawn		
HV - screws	(6914)	14399 - 4		
HV - nuts	(6915)	14399 - 4		
HV - washers	(6916)	14399 - 6		

Hexagon flange screws	(6921)		1665	
Hexagon flange screws and reduced shaft	(6922)		1665	
Hexagon flange nuts	(6923)		1661	
Locking nut (non-metal insert)	(6924)	10512		
typ 1, metric fine thread				
Locking nut (non-metal insert)	(6924)	7040		
typ 1				
Tolerance zone				
Locking nut (full-metall) typ 2	(6925)	7042		
Locking nut (full-metall) typ 2	(6925)	10513		
metric fine thread				
Locking flange nut	(6926)		1663	
(non-metal insert)				
Locking flange nut	(6926)		1666	
(non-metal insert) metric fine thread				
Locking flange nut (full-metall)	(6927)		1664	
Locking flange nut (full-metall) metric fine thread	(6927)		1667	
Hexagon head tapping screws with flange	6928	7053		
Blind rivet	(7337)	withdrawn and replaced		
Rivet flat head AIA/ST	(7337)	15977		
Rivet countersunk head AIA/ST	(7337)	15978		
Rivet flat head ST/ST	(7337)	15979		
Rivet countersunk head ST/ST	(7337)	15980		
Rivet flat head AIA/AIA	(7337)	15981		
Rivet countersunk head AIA/AIA	(7337)	15982		
Rivet flat head A2/A2	(7337)	15983		
Rivet countersunk head A2/A2	(7337)	15984		
Cu/Br or CU/SSt	(7337)	16582		
Cu/Br or CU/SSt	(7337)	16583		
or NiCu/SSt	(7337)	16584		
Spiral split pin	(7343)	8750		

Spiral split pin, heavy, slotted	(7344)		8748		
Spring pins (-sleeves) slotted, leight-weight type	(7346)		13337		
Self drilling screws - thread- mechanical and	(7504)		10666		
functional proberties					
Self drilling screws, hexagon head with flange	(7504)		15480		
Self drilling screws, flat head cross recess	(7504)		15481		
Self drilling screws, countersunk head cross recess	(7504)		15482		
Self drilling screws, raised countersunk head cross recess	(7504)		15483		
Screws with standard thread	(7964)	1	without substitution withdraw	n .	
Self locking nuts	(7967)	\	without substitution withdraw	n .	
Self-tapping screws cylinder head with slot	(7971)	1481	1481		
Self-tapping screws countersunk head with slot	(7972)	1482	1482		
Self-tapping screws raised countersunk head with slot	(7973)	1483	1483		
Self-tapping screws hexagon head	(7976)	1479	1479		
Taper pins with threaded stem	(7977)			28737	
Parallel pins with inside thread, unhardened	(7978)			28736	
Parallel pins with inside thread, hardened	(7979)		8735		
Parallel pins with inside thread, unhardened	(7979)		8733		
Tolerance zone					
Circlips for cylinder head screws	(7980)	١	without substitution withdrawn		
Self-tapping screws pan head cross recess	(7981)	7049	7049		
Self-tapping screws countersunk head cross recess	(7982)	7050	7050		
Self-tapping screws raised countersunk head cross recess	(7983)	7051	7051		
Raised cheese head screws cross recess	(7985)		7045		
Counter sunk screw internal hexagon	(7991)		10642		
Hexagon fit bolt, high-strengh	(7999)			14399-8	
flat washers big series part 1 productclass A	(9021)		7093-1		
flat washers big series part 2 productclass C	(9021)		7093-2		
Snap ring see DIN 7993	(9045)	,	without substitution withdrawn		
Weld end for turnbuckle	34828		with DIN 1480:2005;		
			alternative for DIN		
			1480:1975		
Tolerance zone					

Cylinder head screws cross recess	none	7048	
Locking nut (full-metall) typ 1	none	7719	
Groove pins half length nicked	none	8743	
Spral split pin, slightly	none	8751	
Shoulder - fit bolt	none	7379	
Flat head screws with internal hexagon	none	7380	
Button head socked screws (flattened) - part 1 flattened button head (head type A)		7380-1	
Button head socked screws (flattened) - part 1 flattened button head with flange (head type B)		7380-2	
Hexagon flange screws	none		1662
Hexagon flange screws fine thread	none		14219
Hexagon flange nuts - fine thread	none		14218
Hexagon screws	none		24015
socket head cap screws, metric, fine thread	DIN EN ISO 21269	12474	
Cylinder screws with I-star	none	14579	
Cylinder screws with I-star, low head	none	14580	
Flat head screws with I-star	none	14583	
Raised countersunk screws with I-star	none	14584	
Flat head tapping screws with I-star	none	14585	
Self-tapping screws countersunk head I-star	none	14586	
Self-tapping screws raised countersunk head I-star	none	14587	
Rivet flat head AIA/ST	none	15973	
Rivet countersunk head AIA/ST	none	15974	
Rivet flat head AIA/ST	none	15975	
Rivet flat head AIA/ST	none	15976	
Rivet flat head ST/ST	none	16585	

This elaboration has been put up to the best of our quality assurance department's knowledge (stage of affairs: March 2011). We cannot accept any guarantee concerning exhaustiveness and accuracy. Details about the change of standards please see in technical literature of Beuth publishing company.